


SWARM: current status & a bright future. . .




Jonathan Weintroub



for the SWARM Development Team

SMA Science in the Next Decade, ASIAA, Taiwan

27 October 2016



. . .Or:

Behold the Power of SWARM

Glen

[reply](#) [#32493](#)

Category: General


Antennas: 1,3,4,5,6,7,8

entered by: gpetitpa

LO Frequency: 343 GHz

RMS: 0.49 mJy (contours=3,4,5 sigma)

Beam=0.92x0.63"



ack taken in dual-rx SWARM-only mode on Sunday night. The tau
ne phase was OK considering we are in EXT. Both the 345s and
lz USB (LO = 343 GHz). The pointing on Antenna 7 was poor, and
ies, the 400s on Antenna 7 were basically unusable.

ugh the calibration I find that the rms of *each* 6 GHz wide
s around 1 mJy when I image them individually (the 400 images
i the flagging of Antenna 7). Combining all the data into a full
a **dirty map with an rms of 0.55 mJy (550 uJy)**.

ertain because Uranus was resolved on most baselines and I did
I assumed a scale factor of '1' for baselines with no useful Uranus
| scale factors of 1-1.3, and I am not 100% certain that the tsys


correction for SWARM is as good as it used to be for ASIC.

The target (as calibrated) has a flux of 2.35 mJy and is detected at the 4.3 sigma level. This would have been around a 2.5 sigma detection with just the ASIC.

For comparison, the online sensitivity calculator (assuming 1 mm BWA) gives 1.02 mJy per 2

Shed a tear . . .

The ASIC correlator was shut down about a week ago, it served SMA well
(presentation time is far too valuable for a minute of silence)



Mark 4 XF 'CB'
(Canaris ASIC from late 1990's)

90 CBs in system
32 ASICs/CB = 2880 ASICs/system

~25 kW digital+analog+cooling



IF downconverter and sampler assembly (C2DC)

8 antennas x 6 'blocks' x 2 pols = 96 assemblies

96 x 4 chunks/block
= 384 IF channels and ADCs

- Highly hybridized, 4 GHz band divided into 48 'chunks' per antenna.
- SMA ASIC was XF architecture, in common with many others, including ALMA
- We now strongly favor FX architecture, supported by FPGA DSP technology.

ASIAA 5 GSa/s sampler is foundational wideband technology

(Jiang et al., PASP 126, 761; 2014; Patel et al., JAI 3, 1 2014)




Ultra Fast Analog-to-Digital Converters are typically interleaved multi-core devices

This introduces interleaving artifacts which must be calibrated

CASPER ROACH2 with Dual ASIAA ADCs

as configured for SWARM


Photo by Derek Kubo



(For more on CASPER see Hickish et al., JAI, 2016, in review)

SWARM: SMA Wideband Astronomical ROACH2 Machine


(Primiani et al., JAI, 2016, in review)



1 "quadrant": 2 GHz per receiver per sideband = 8 GHz; 32 GHz total

Benefits relative to ASIC correlator:


1. high uniform spectral resolution with no sacrifice of bandwidth,
2. smaller footprint and power consumption.
3. better digital efficiency with 4-bit cross-correlation
4. 2 GHz wide bands easier to reduce, result in higher quality spectra
5. Natively supports VLBI phasing and recording, 16 Gbps/quadrant
6. Built with COTS components



“FGPA Utilization”: fine spectral resolution requires large FFTs will all the SWARM logic fit?

(Primiani, Weintroub, deWerd, 2011,

https://www.cfa.harvard.edu/twpub/SMAwideband/MemoSeries/sma_wideband_utilization_1.pdf)




$$M_{\text{PFB}} = \underbrace{D \log_2 ND}_{\text{FFT}} + \underbrace{TD}_{\text{FIR}} - \underbrace{2D}_{\text{optimization}}$$

Example calculation of “instantiated multipliers” needed in FPGA for large “polyphase filterbank” (a type of FFT with improved isolation)

SWARM FPGA logic subsumes great complexity

Primiani et al., JAI, 2016, in review




SWARM is EHT-ready

Phased ALMA to SMA Fringe, 22 Jan 2016
 2015, 2016 annual campaigns observed and fringes verified.


Mk4/DiFX fourfit 3.11 rev 1291

3C454_3.ypukrr, No0018, AS

ALMA - SMAP, fgroup B, pol YL



**Geoff Crew, Mike Tttus,
 Roger Cappallo, Adam Deller,
 ALMA phasing Geoff Crew and
 Lynn Matthews, and many more!**




**A. Young, Primiani, K. Young,
 Weintroub, et al., IEEE Phased
 Array Conference, October 2016**

SMA phasing efficiency on various sources, EHT campaign
 4 April 2016

(talk by Keiichi Asada, this workshop, on EHT)

A 4-bit correlator is more efficient than 2-bit

SiO maser in R-Cas was used to measure the ratio of SWARM/ASIC SNR.



ASIC SiO line is red. SWARM line is green.

By measurement, SWARM SNR is 11 +/- 3% better

SMA's Future Upgrade: From 32 GHz to 56 GHz total BW

(14 GHz per pol per sideband; Grimes, et al., prior talk)

- Simply keep building until seven SWARM “quadrants”?
- That may be the the fastest “time to science”
- Safe and conservative; however, rather unimaginative
- What is the rationale to stretch our in-house technology?

SMA's Future Upgrade: From 32 GHz to 56 GHz total BW



North American
ALMA Science
Center



its”?

Development Upgrades of the Atacama Large
Millimeter/submillimeter Array (ALMA)

e

ogy?

Study Proposal Form

STUDY PROPOSAL TITLE:

DIGITAL CORRELATOR AND PHASED ARRAY ARCHITECTURES FOR UPGRADING ALMA

PRINCIPAL INVESTIGATOR: JONATHAN WEINTROUB

INSTITUTION: SMITHSONIAN ASTROPHYSICAL OBSERVATORY

Digital Correlator and Phased Array Architectures for upgrading ALMA



N.A. ALMA Development Study awarded to SAO
Study team kick off meeting at CfA, 10, 11 May 2016



A 10 GSa/s single core CASPER ADC from ASIAA

based on Adantec ANST7120A-KMA

Jiang, Yu & Guzzino (2016)



Homin Jiang, ASIAA, with 10 Gsps ADC, yesterday




Analog frequency response 0 to 5 GHz

SKARAB: SKA Reconfigurable Application Board

(designed for MeerKAT by Peralex, South Africa, based on Virtex7 VX690T)



Henno Kriel, MeerKAT DSP engineer & CASPERite, with SKARABs
August 2016, Pinelands, South Africa



SKARAB: SKA Reconfigurable Application Board

(designed for MeerKAT by Peralex, South Africa, based on Virtex7 VX690T)



ADSANTEC

Ultra High-Speed Mixed Signal ASICs

*Advanced Science And Novel Technology Company, Inc.
27 Via Porto Grande, Rancho Palos Verdes, CA 90275*

*Offices: 310-377-6029 / 310-803-9284 Fax: 310-377-9940
www.adsantec.com*

ASNT7122-KMA

15GS/s, 4-bit Flash Analog-to-Digital Converter with HS Outputs



- 20GHz analog input bandwidth
- Selectable clocking mode: external high-speed clock or internal PLL with external reference clock
- Broadband operation in external clocking mode: DC-15GS/s
- On-chip PLL with a central frequency of 10GHz
- Selectable on-chip PRBS $2^{15}-1$ generator for output data scrambling
- Differential CML input clock buffer and output data and clock buffers
- Differential linear data input buffer
- LVDS input reference clock buffer
- Selectable on-chip digital-to-analog converter for self-testing

SAO 20 GS/s ADC based on Hittite HMCAD5831LP9BE, single core


(Weintroub and Raffanti, ISSTT, 2015)

Funded by SI Competitive Grants Program for Science

“sparkle codes” ~ 1 in 1000 frequency



persistence display



VC709 Xilinx V7 Evaluation Board
bargain basement price: \$4995


SERDES Transceivers:
GTP, GTX, **GTH**, GTZ

GTH features:

- 7 tap decision feedback equalizer (DFE) vs 5-tap for GTX
- Rx reflection cancellation
- In the Tx, the "Phase Interpolator PPM Controller" which allows fine-grain adjustment of the Tx phase

2 to 8.2 GHz Noise passband

power spectrum of 3-bit sampled noise




The best way to predict the future is to create it

Abraham Lincoln

- All goals for SWARM set at project inception are met
- Engineering decisions made at the outset are validated:
 - Quad-Core wideband ADC technology for science-quality data
 - Full featured FPGA logic with ability to project required resources
 - Fit in FPGA a hi-res FX correlator with EHT phasing and recording
 - And more . . .
- The future is bright:
 - Quad4 build will complete 32 GHz SWARM this calendar year...
 - ...then develop and access yet wider band ADC, FPGA technology...
 - ...apply our expertise to upgrade ALMA...
 - ...and build skills and capacity in DSP for broad application!

Questions?



Orion BN/KL line forest plot from Primiani et al., JAI, 2016, in review

Questions?


“With correlator performance having gone up by a factor of 922,000 over the last 30 years, its only fair that correlator design engineers' salaries should have gone up by a similar factor”

Ray Escoffier, leader of N.A. ALMA correlator team, over a decade ago


Questions?

- THE VERY LARGE TELESCOPE
- THE EXTREMELY LARGE TELESCOPE
- THE OVERWHELMINGLY LARGE TELESCOPE (CANCELED)
- THE OPPRESSIVELY COLOSSAL TELESCOPE
- THE MIND-NUMBINGLY VAST TELESCOPE
- THE DESPAIR TELESCOPE
- THE CATAclySMIC TELESCOPE
- THE TELESCOPE OF DEVASTATION
- THE NIGHTMARE SCOPE
- THE INFINITE TELESCOPE
- THE FINAL TELESCOPE

supplementary material




APHIDS Interpolation and inversion software



- **APHIDS is GPU-accelerated post processing software built on #1 by Dave MacMahon,** developed primarily by *André Young* and Katherine Rosenfeld, with help from Lindy Blackburn and Rurik Primiani.
- <https://github.com/david-macmahon/hashpipe>)
- APHIDS converts spectral-domain SWARM data to the equivalent time-domain R2DBE data, which includes resampling, filtering, and frequency conversion.
- GPU acceleration means the ultimate goal of real-time on-the-fly “may be possible”.

The Importance of Phase



Oppenheim
& Lim, 1981

